MC342dn/MC342dnw Specifications





The MC342dn is the perfect device for the micro business or home office with low usage and print volume requirements providing a variety of functions and a flexibility of printing, scanning, copying and faxing. With colour print speeds of 20ppm and mono print speeds of 22ppm, the MC342dn can easily manage printing your marketing materials in-house.

And, for added versatility the MC342dnw model offers wireless connection that allows you to place your MFP wherever is most convenient.

The MC342dn/MC342dnw are built on tried and tested technology that your business can rely on to deliver over and over again, supported by a 3-year warranty.

Outstanding features to support your business needs

- Automatic Duplex printing, copying, and scanning as standard with colour print speeds up to 20ppm
- 50-sheet Reverse Automatic Document Feeder for quick and easy copying and scanning double-sided documents
- Time to first print, 9 seconds colour, 8.5 seconds mono
- Intuitive menus and controls with one touch function buttons and 3.5" LCD display for simple user interface
- Print directly from or scan directly to a USB stick

Outstanding print quality and media flexibility

- Duplex as standard (up to 176gsm), for in-house professional printing
- ProQ2400 multi-level output quality, 1200 x 600dpi print resolution
- Microfine High Definition toners for superb print quality
- Flexible media handling: from A6 to 1320mm banners; card stock up to 220gsm
- OKI Template Manager makes it easy to format and print various documents in-house

Functionality to improve your productivity and workflow

- High quality copying and scanning using LED digital technology
- Overlay function enables you to save logos or forms in the MFP memory, for re-use in other documents
- Send faxes over the internet
- Fast scan speed of up to 20ppm colour and 30ppm mono
- USB and network TWAIN scanning (PC and Mac)
- LDAP direct access to contact and email data from an existing server directory
- Multiple copying and scanning configurations with single or double sided output
- ID card copying for simple copying of double sided ID cards on a single sheet


- Document collation automatically sorts copies of multi-page documents
- Mobile printing print effortlessly from your smartphone or tablet. This printer is Google Cloud Print Ready, as well as being compatible with AirPrint by Apple Inc, Cortado Workplace and ePrint by Microtech Corp, enabling you to print where ever you are, without having to connect directly to a printing device

Efficient and cost saving functionality

- Eco mode improves throughput performance and reduces energy consumption
- Deep Sleep mode reduces energy consumption to less than 1.5W
- Auto-Off mode automatically powers down from Deep Sleep, reducing energy consumption to 0.5W when not in use
- Free consumables recycling programme

Useful utilities that help you control and manage your printing

- PrintSuperVision helps you control and resolve issues with printers across your networks
- Print Job Accounting provides visibility and control of your organisation's print spend across your network





MC342dn/MC342dnw - Colour and Mono Multifunction Products

PRINTER		Typefaces	
A4 Print speed	20ppm colour, 22ppm mono	Printer fonts	Scalable: 87 PCL Fonts and 80 PostScript fonts; PCL Bitmap
Time to first print	9 seconds colour, 8.5 seconds mono		fonts: Lineprinter OCR-A/B, USPS ZIP Barcode
Warm up time	Up to 60 seconds from power on and up to 32 seconds from power save	Barcode	11 types of one dimension with 27 variations: UPC-A, UPC-E, EAN/JAN-8, EAN/JAN-13, Interleaved2of5, Code39, Code 128, EAN/UCC-128, CODABAR, ZIP+4POSTNET, Customer barcode; 1
Processor speed	533MHz		type of two dimension: PDF417
Scanner		PRINT QUALITY	
Optical Resolution	1200 x 1200dpi	Resolution	ProQ2400 Multi-level Technology, 1200 x 600dpi, 600 x 600dpi
Speed	Up to 20ppm colour, up to 30ppm mono	Enhancements	Auto Color Balance, Photo Enhance via driver
Colour depth	Input 48-bit / Output 24-bit		(excludes PostScript driver)
Document input	50-sheet Reverse Automatic Document Feeder (RADF), flatbed scanner	PAPER HANDLING Paper capacity	Tray 1: 250 sheets of 80gsm; Multi-purpose tray: 100 sheets
Contrast	7 Levels		of 80gsm; RADF: 50 sheets of 80gsm
Format	PDF, M-TIFF, JPEG, XPS	Maximum paper capacity	350 sheets of 80gsm
Address book	LDAP, 100 E-mail address, 20 group addresses		Tray 1: A4, A5, B5, A6; Multi-purpose tray: A4, A5, B5, A6, Envelopes (C5, DL, Com-9, Com-10, Monarch), Index Card (3" x 5") (75 x 125mm), Photo Size (4" x 6", 5" x 7") (100 x 150mm, 125 x 175mm), Custom Size (up to 1320mm length including banners); Duplex: A4, A5, B5; RADF: A4, A5, B5, A6
Scan to COPY	FTP, HTTP, USB memory, E-mail, TWAIN, CIFS	Paper sizes	
First copy out	Less than 14 seconds colour, less than 12 seconds mono	Paper weight	Tray 1: 64 to 176gsm; Multi-purpose tray: 64 to 220gsm;
Speed	Up to 20cpm colour and up to 22cpm mono		Duplex: 64 to 176gsm; RADF: 60 to 105gsm
Resolution	Up to 600 x 600dpi	Duplex	Standard
Reduction / Enlargement	Zoom 25-400%	Paper output	Face Down: 150 sheets of 80gsm; Face Up: 100 sheets of 80gsm
Maximum copies	99	GENERAL FEATURES	
FAX		Memory	Standard RAM: 256MB; Maximum RAM: 768MB
Connectivity	RJ11 x 2 (Line/Tel), PSTN, PBX Line	Environment	Operating temperature/ humidity: 10°C to 32°C (17°C to 27°C recommended)/ 20% to 80% RH (50% to 70% RH recommended)
Speed	ITU-T G3(Super G3) up to 33.6kbps, 3 seconds/page	Environment	Storage temperature/ humidity: -10°C to 43°C/ 10% to 90% RH
Fast dialing		Power supply	Single phase 220 to 240VAC, frequency 50-60Hz +/- 2%
Groups	•		Typical: 500W; Max: 1170W; Idle: 100W; Power Save: <20W;
Broadcast Page memory		Power consumption	Deep Sleep: <1.5W; Auto-Off: <0.5W
OPERATOR PANEL		Noise level	Operating: 52dB(A) or less (copy); Standby: 33dB(A); Power save: Inaudible
LCD Panel	Single simplified blue backlit graphics panel:	Dimensions (HxWxD)	444 x 427 x 509mm
	84.1mm (W) x 33.6mm (H); Resolution: 320x128 dots	Weight ⁴	<29kg approx
Key pad	12 alpha/numeric keys, 3 main function buttons (Copy, Scan, Print), Color & Mono Start, Status, Setting, Help, 6 main navigation buttons (Back, Up, Down, Left, Right, OK), Clear, Stop, Power Save, Reset/Log Out	Duty cycle	Maximum: 30,000 pages/month; Recommended: Up to 2,000 pages/month
		Warranty	3 years extended warranty upon registration within 30 days of purchase
INTERFACE AND SOFTWARE		Product order numbers	MC342dn: 44952134; MC342dnw: 44952143
Connectivity	10/100 TX Ethernet, USB 2.0 Device IF, USB 2.0 Host IF		
Printer languages	PCL6 (XL3.0), PCL5c, PostScript 3 emulation, SIDM (IBM-PPR, EPSON-FX)	Accessories (Order Number	256MB: 01182907; 512MB: 01182908
Network & protocols	MC342dn, MC342dnw: All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IPv4&v6, SMTP, POP3, HTTP, SMMPV1&v3, DHCP, DNS, LPR, Port9100, BOOTP, ARP, FTP, CIFS, LDAP, SLP, Bonjour. NetWare, EtherTalk, NetBEUI, LLTD, Web Service on Devices, AirPrint, Google Cloud Print. MC342dnw: Wireless LAN Protocol (IEEE802.11b, IEEE802.11g, IEEE802.11n, Infrastructure Mode, WEP, WPA(TKIP), WPA2(AES), WPS-PBC, WPS-PIN, Open system authentication, Shared key authentication, IEEE802.1x authentication)	Memory	230mb. 01102)07, 312mb. 01102)00
		CONSUMABLES (ORDER NUMBE	
			Black: 44973536
		Toner cartridges* (1,500 pages)	Cyan: 44973535; Magenta: 44973534; Yellow: 44973533
		Image drum**	44968301
		Transfer Belt	44472202
OS Compatibility ¹	Windows XP (32-bit & 64-bit) / Server 2003 (32-bit & 64-bit) / Server 2008 (32-bit & 64-bit) / Server 2008 R2 (64-bit) / Vista (32-bit & 64-bit) / Windows 7 (32-bit & 64-bit) / Windows 8 (32-bit & 64-bit); Mac OS X 10.3.9 to 10.8	(60,000 pages) Fuser Unit (60,000 pages)	44472603
Advanced networking & security	IP Filtering, MAC Filtering, SSL/TLS, NIC Driver (IC+), WindowsRally EmailAlert, EAP(IEEE802.1X), IPSec	*Toner: A4 pages yield compliant with ISO/IEC 19798. Printer shipped with toner for 750 A4 pages **Drum: Average life of 3 pages per job from tray 1 in simplex mode.	
Utility suite ¹	Template Manager ² , Color Correct, OKI LPR ² , Color Swatch Utility ² , PrintSuperVision.net ² , PrintSuperVision Multiplatform ² , Print Job Accounting Server ² , Print Job Accounting Client, Web Driver Installer ² , Network Card Setup, Configuration Tool ² , ICC Color Profiles, PS Gamma Adjuster, Profile Assistant ³ , PDF Direct Print ² , Actkey ²	(30,000 pages black, 20,000	pages colour)

 $^{1}\text{Check local OKI website for latest driver releases and OS compatibility; }^{2}\text{Windows only; }^{3}\text{Mac only; }^{4}\text{Including all consumables}$

Consumables Information: For the protection of your printer, and in order to ensure that you benefit from its full functionality, this model has been designed to operate only with genuine OKI toner cartridges. These can be identified by the OKI trademark. Any other toner cartridge may not operate at all, even if it is described as "compatible", and if it does work, your printer's performance and print quality may be degraded.



3 Year Warranty

Our devices are manufactured to the highest standards of quality and technology, which has been confirmed by independent tests. We are so convinced of the high quality of our products that we are offering you an extension of the standard warranty period to 3 years at no extra cost. Simply register your product within 30 days of purchase to be eligible for our unique all inclusive offer. For further information please visit: www.oki.co.uk/warranty. Without registration, the standard pan-European 1 year warranty applies.

OKI EUROPE LTD.

Blays House, Wick Road Egham, TW20 0HJ United Kingdom T +44(0) 20 8219 2190 F +44(0) 20 8219 2199 WWW.OKIEUROPE.COM







Document management Nuance PaperPort SEv11, Nuance OmniPage SEv16





